

Standard alloys

C35300 Brass

Quality and consistency allows customers to produce more components per hour, maintain tighter tolerances, and reduce costs through longer tool life.

Advantages

- Excellent machinability
- 100% recyclable
- Good corrosion resistance
- High productivity alloy
- Longer tool life

Application: maching and cold forming

ASTM: B453

Lengths: 10 to 16 feet

Bundle weights: 1,000 - 4,000 lbs.

| Chemistry composition | | | | | |
|-----------------------|----------|-----------|-----------|--|--|
| Cu | Pb | Fe | Zn | | |
| 61.0-63.0% | 1.5-2.5% | 0.15% max | Remainder | | |

| Minimum mechanical properties | | | | | |
|-------------------------------|------------------------------|----------------------------|-----------------|----------------------------------|--|
| Diameter (inch) | Tensile strength (ksi) | Yield strength (ksi) | Elongation % | Hardness (Rb) (mid-radius) | |
| >0.250" | 57 | 25 | 7 | - | |
| 0.500"-1.000" | 55 | 25 | 10 | 60-80 | |
| >1.000"-2.000" | 50 | 20 | 15 | 50-75 | |
| >2.000" | 50 | 20 | 15 | 40-70 | |



| Round 0.250" - 4.50" | Hex / RC Hex 0.250" - 2.50" |
|----------------------------|--|
| Square 0.250"-2.00" | Shapes Cross section up to 2.50" |

| Diameter tolerances +/- | | | | |
|-------------------------|---------|-------------------------|--|--|
| Diameter (inch) | Round | Hexagonal, Octagonal | | |
| >0.250"-0.500" | 0.0015" | 0.0030" | | |
| >0.500"-1.000" | 0.0020" | 0.0040" | | |
| >1.000"-2.000" | 0.0025" | 0.0050" | | |
| >2.000" | 0.15% | 0.30% | | |